


**ALL 2K BIT (256 BYTE) ICLASS CREDENTIALS HAVE THE FOLLOWING FEATURES:**

- Available in two application area configuration only.
- Provides the HID standard access control application area and one other application area for user customization.
- Meet ISO 15693 standard for contactless communications.
- Provides a cost effective way to improve the security of your access control installation.

ALL 16K BIT (2K BYTE) ICLASS CREDENTIALS HAVE THE FOLLOWING FEATURES:

- Sufficient read/write memory to store multiple biometric templates.
- 16k available in a two or sixteen application area configuration.
- Multiple securely separated files enable numerous applications, including the HID standard access control application, and support future growth.
- Meets ISO 15693 for contactless communications.

CONTACTLESS SMART ADHESIVE TAG • 2060, 2061, 2062

HID's iCLASS[®] 13.56 MHz Embeddable read/write contactless smart card technology can be used for diverse applications such as access control, biometrics, cashless vending, public transportation, airline ticketing and customer loyalty programs. Multiple, securely separated files enable numerous applications and support future growth.

The iCLASS Tag provides the convenience of iCLASS technology in a coin-sized, disk-shaped transponder that can be simply attached to any nonmetallic card or device to instantly have 13.56 MHz read/write contactless smart card technology to utilize as a transition device during the rebadging process. You can seamlessly upgrade from Wiegand, magnetic stripe or barium ferrite technologies and can easily and costeffectively turn an existing plastic ID badge or contact smart card into a contactless proximity credential.

Features:

- 13.56 MHz read/write contactless smart card technology provides high-speed, reliable communication with high data integrity.
- iCLASS technology is designed to provide security with mutual authentication, encrypted data transfer, and 64-bit diversified keys for read/write capabilities.
- Any existing HID format can be factory or field programmed into the secure HID access control application area.
- Available in 2k bit (256 Byte) or 16k bit (2k Byte) configurations.

READ/WRITE FUNCTIONALITY FOR MULTI-FUNCTIONAL MEMORY APPLICATIONS

iCLASS® was specifically designed to make access control more powerful, more versatile, and more secure. All radio frequency data transmission between the card and reader is encrypted using a secure algorithm. By using advanced encryption techniques, iCLASS reduces the risk of compromised data or duplicated cards. For even higher security, the card data may also be protected with DES or triple DES encryption. Multiple securely separated application areas are each protected by 64-bit diversified read/write keys which allow complex applications and provide for future expansion.

Security mechanisms such as mutual authentication and encryption are efficiently combined with fast processing and data communication,

resulting in transaction times of less than 100 milliseconds for a typical secure e-purse transaction.

PROVEN, RELIABLE TECHNOLOGY

Offers extremely consistent read range. Unaffected by body shielding or variable environmental conditions.

LONG LIFE

Passive, no-battery design allows for an estimated minimum 100,000 reads.

DURABILITY

Strong, flexible, and resistant to cracking and breaking.

SPECIFICATIONS

Base Part Numbers		2060 for 2k bit (256 Byte) card with 2 application areas 2061 for 16k bit (2k Byte) card with 2 application areas 2062 for 16k bit (2k Byte) card with 16 application areas
Description	13.56 MHz contactless smart adhesive tag.	
Typical Maximum Read Range*	R10 1.0" (2.5 cm) R30/RW300 1.0" (2.5 cm) R40/RW400 1.0" (2.5 cm) RK40/RWK400 1.0" - 1.5" (2.5 cm - 3.8 cm) *Dependent upon installation conditions.	
Dimensions	Diameter: 1.285" (3.264 cm) Thickness: 0.070" (0.178 cm)	
Weight	0.04 oz. (1.18 g)	
Outer Shell Material	Lexan	
Operating Temperature	-40° to 158° F (-40° to 70° C)	
Operating Humidity	5-95% non-condensing	
Operating Frequency	13.56 MHz	
RF Interface	As suggested by ISO/IEC: 15693 read/write	
Transaction Time	<100 ms typical	
Baud Rate	15693 mode - 26 kbps	
Memory Type	EEPROM, read/write	
Multi-application Memory	2k bit (256 Byte) tag - 2 application areas 16k bit (2k Byte) tag - 2 or 16 application areas	
Write Endurance	Min. 100,000 cycles	
Data Retention	10 years	
Options	External card numbering (inkjet or laser engraving) Custom artwork (text or graphics) Color - Textured, matte, gray, or black (Please see "How To Order Guide" for a description of the options and associated part numbers.)	
Warranty	Lifetime Warranty. See complete warranty policy for details.	

© 2024 HID Global Corporation. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design and iCLASS are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2024-03-13-pacs-iclass-tag-ds-en

PLT-00235



Learn about HID Global's green initiatives
hidglobal.com/green



hidglobal.com

North America: +1 512 776 9000
Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +44 1440 714 850
Asia Pacific: +852 3160 9800
Latin America: +52 55 5081 1650

An ASSA ABLOY Group brand

ASSA ABLOY