

iCLASS SE® eUnit

iCLASS SE® insert 207X • 2070,
2071, 2072, 2073, 2074

HID's iCLASS SE 13.56 MHz read/write contactless smart card technology can be used for diverse applications such as access control, biometrics, cashless vending, public transportation, airline ticketing and customer loyalty programs. Multiple, securely separated files enable numerous applications and support future growth.

The iCLASS SE eUnit provides the convenience of iCLASS SE technology in a coin-sized, disk-shaped transponder that can be inserted into any nonmetallic card or device to instantly provide 13.56 MHz read/write contactless smart card technology capabilities to utilize as a transition device during the rebadging process.

FEATURES:


- 13.56 MHz read/write contactless smart card technology provides high-speed, reliable communications with high data integrity.
- iCLASS technology is designed to provide security with mutual authentication, encrypted data transfer, and 64-bit diversified keys for read/write capabilities.
- Any existing HID format can be factory- or field-programmed into the secure HID access control application area.
- Available in 2k bit (256 Byte), 16k bit (2k Byte) or 32k bit (4k Byte) configurations.

ALL 2K BIT (256 BYTE) iCLASS SE CREDENTIALS HAVE THE FOLLOWING FEATURES:

- Available in two application area configuration only.
- Provides the HID standard access control application area and one other application area for user customization.
- Meet ISO 15693 standard for contactless communications.
- Provides a cost effective way to improve the security of your access control installation.

ALL 16K BIT (2K BYTE) AND 32K BIT (4K BYTE) iCLASS SE CREDENTIALS HAVE THE FOLLOWING FEATURES:

- Sufficient read/write memory to store multiple biometric templates.
- 16k Available in a two or sixteen application area configuration. 32k available with 16k memory configured in either 2 or 16 application areas, plus an additional 16k user configurable memory.
- Multiple securely separated files enable numerous applications, including the HID standard access control application, and support future growth.
- Meet ISO 15693 for contactless communications.



KEY BENEFITS:

- **13.56 MHz technology** – High speed, reliable communications with high data integrity
- **Convenience and security of iCLASS SE® technology** – Disk-shaped transponder for OEM use
- **Versatile** – Available in 2k bit, 16k bit or 32k bit configurations

* Due to variations in card and reading devices, HID does not claim that the iCLASS SE eUnit will work in every situation. Functional and nonfunctional iCLASS SE eUnits are available for compatibility testing with existing credential and reader technologies. Compatibility should be confirmed prior to ordering.

READ/WRITE FUNCTIONALITY FOR MULTI-FUNCTIONAL MEMORY APPLICATIONS

iCLASS SE® was specifically designed to make access control more powerful, more versatile and more secure. By using advanced encryption techniques, iCLASS SE reduces the risk of compromised data or duplicated cards. All radio frequency data transmission between the card and reader is encrypted using a secure algorithm. For even higher security, the tag data may also be protected with DES or triple-DES encryption. Multiple securely separated application areas are each protected by 64-bit diversified read/write keys which allow complex applications and provide for future expansion.

Security mechanisms such as mutual authentication and encryption are efficiently combined with fast processing and data communication, resulting in transaction times of less than 100 milliseconds for a typical secure e-purse transaction.

PROVEN, RELIABLE TECHNOLOGY

Offers extremely consistent read range. Unaffected by body shielding or variable environmental conditions.

LONG LIFE

Passive, no-battery design allows for an estimated minimum 100,000 reads.

Base Part Numbers	2070 for 2k bit (256 Byte) card with 2 application areas 2071 for 16k bit (2k Byte) card with 2 application areas 2072 for 16k bit (2k Byte) card with 16 application areas 2073 for 32k bit (4k Byte) 16k/2+16k/1 2074 for 32k bit (4k Byte) 16k/16 + 16k/1
Description	13.56 MHz iCLASS SE eUnit
Dimensions	Diameter: 0.749" (19,02mm) Thickness: 0.017" (0,4318mm)
Weight	0.20 oz. (5.7g)
Operating Temperature	-40° to 158° F (-40° to 70° C)
Operating Frequency	13.56 MHz
RF Interface	As suggested by ISO/IEC: 15693 read/write
Transaction Time	<100 ms typical
Baud Rate	15693 mode - 26 kbps
Memory Type	EEPROM, read/write
Multi-application Memory	2k bit (256 Byte) card – 2 application areas 16k bit (2k Byte) card – 2 or 16 application areas 32k bit (4k Byte) card – 16k bits in 2 or 16 application areas plus 16k bits user configurable.
Write Endurance	Min. 100,000 cycles
Data Retention	10 years
Warranty	See complete warranty policy for details.



hidglobal.com

North America: +1 512 776 9000 | Toll Free: 1 800 237 7769
Europe, Middle East, Africa: +353 91 506 900
Asia Pacific: +852 3160 9800 | Latin America: +52 55 9171 1108
For more global phone numbers click here

© 2024 HID Global Corporation/ASSA ABLOY AB. All rights reserved.
2024-03-08-pacs-iclass-se-eunit-ds-en PLT-05951
Part of ASSA ABLOY