

▼ Tips for Discontinued Irons

Replacement Tips For Older Micron® Soldering Irons



Standard Soldering Tips

Price Each	Suits	Size (mm)	Type	RRP	5+
T 2412	T 2444	0.8	Chisel	12.50	11.25
T 2413	T 2444	1.6	Chisel	12.50	11.25
T 2414	T 2444	3.2	Chisel	12.50	11.25
T 2421	T 2443/6	0.4	Chisel	14.50	12.95
T 2430	T 2443/6	0.8	Chisel	14.50	12.95
T 2431	T 2443/6	1.6	Chisel	14.50	12.95
T 2432	T 2443/6	3.2	Chisel	14.50	12.95
T 2433	T 2438/42	0.2	Round	20.75	20.75
T 2434	T 2438/42	0.8	Round	12.50	11.25
T 2435	T 2438/42	1.6	Chisel	12.50	11.25
T 2436	T 2438/42	3.2	Chisel	12.50	11.25
T 2085	T 2080	1.0	Chisel	37.95	35.50
T 2086	T 2080	2.0	Chisel	35.75	32.95
T 2087	T 2080	3.0	Chisel	35.75	33.50
T 2406	T 2401/5	1.0	Round	4.55	3.60
T 2407	T 2401/5	3.0	Chisel	4.55	3.60
T 2410	T 2409	1.0	Round	5.20	4.60
T 2411	T 2409	3.0	Chisel	5.20	4.60
T 2463	T 2460	0.5	Round	11.50	10.50
T 2464	T 2460	1.6	Chisel	11.50	10.50
T 2465	T 2460	2.4	Chisel	11.50	10.50
T 2466	T 2460	3.2	Chisel	11.50	10.50

SMD Tweezers (Pairs)

Price Each	Suits	Size (mm)	RRP	5+
T 2392	T 2461	2.0	28.75	26.50
T 2393	T 2461	3.0	28.75	26.50
T 2394	T 2461	5.0	28.75	26.50
T 2395	T 2461	10.0	28.75	26.50

Replacement Tips For Older Micron® Desoldering Tools



Price Each	Suits	Item Type	RRP	4+
T 1265	T 1260	1.2mm Nozzle	26.95	24.50
T 1266	T 1260	1.5mm Nozzle	26.95	24.50
T 1263	T 1260	Filter Set	44.00	40.00
T 1243	T 1242	Nozzle	3.75	3.40
T 1247	T 1246	Nozzle	4.55	4.00

Order online 24/7, 365 days a year!

Easy online ordering at www.altronics.com.au

PDF Downloads

Should you require any additional information on the operation or features of our products, you can find brochures, instructions and information in PDF format online at www.altronics.com.au.

▼ Desoldering Braid

Economy Desoldering Braid



Apply wick to the joint & heat with a soldering iron, capillary action then draws the solder off. 1.5m length.

Price Each		RRP	4+	10+
1.5m rolls				
T 1201A	0.5mm	3.40	3.15	2.90
T 1202A	1mm	3.40	3.15	2.90
T 1204A	1.5mm	3.90	3.15	3.00
T 1205A	2mm	3.90	3.15	3.00
T 1206A	2.5mm	3.40	3.15	2.90
T 1207A	3mm	3.40	3.15	2.90
T 1208A	3.5mm	3.90	3.15	3.00

▼ Solder

Resin Core Solder



All resin core. 60% tin, 40% lead. We recommend this solder for use with soldering irons using iron clad, chrome plated tips. Available in 200g or 1kg rolls, or a handy 3m tube for use in the field.

Price Each		RRP	4+	10+
T 1090	0.5mm 200g roll	34.00	30.00	27.00
T 1095	0.8mm Tube 17gm	4.40	3.95	3.50
T 1100	0.8mm 200g roll	34.00	30.00	27.00
T 1105	0.8mm 1kg roll	163.00	147.00	130.00
T 1120	1mm Tube 17gm	4.95	4.45	3.95
T 1110	1mm 200g roll	34.00	30.00	27.00
T 1115	1mm 1kg roll	163.00	147.00	130.00
T 1122	1.6mm 200g roll	34.00	30.00	27.00
T 1123	1.6mm 1kg roll	163.00	147.00	130.00

Resin Core Lead Free Solder



Lead free. Complies with European RoHS. 99.3% tin, 0.7% copper. Melting point 227°C. We recommend this solder for use with our lead free soldering stations. Available in 250g or 1kg rolls.

Price Each		RRP	4+	10+
T 1072	0.3mm 100g roll	30.50	27.50	24.50
T 1075	0.5mm 250g roll	67.50	60.75	54.00
T 1077	0.8mm Tube 15gm	4.95	4.45	3.95
T 1078	0.8mm 250g roll	67.50	60.75	54.00
T 1079	0.8mm 1kg roll	260.00	234.00	208.00
T 1082	1mm Tube 15gm	4.95	4.45	3.95
T 1080	1mm 250g roll	67.50	60.75	54.00
T 1081	1mm 1kg roll	260.00	234.00	208.00
T 1084	1.5mm 250g roll	67.50	60.75	54.00

500gm Leaded Solder Bar



Quality leaded solder bar for use with solder pots and general electronics construction and repair. 63% Tin, 37% Lead. 500g bar.

Price Each	RRP	4+	10+
T 1139A	59.95	53.95	47.95

▼ Solder Pastes

Chemtools® Solder Paste



Solder paste for use in PCB assembly, prototyping & reflow soldering. Meets Bellcore and IPC requirements. 15g syringe.

Price Each	RRP	4+	10+
H 1640 Leaded	13.25	12.50	11.50
H 1645 Lead Free	18.95	17.75	16.25

Chemtools® No Clean Solder Flux



This flux gel is halogen-free ensuring long-term reliability and ease of soldering. Suitable for both normal and lead-free reflow soldering processes during which the flux medium volatilises leaving minimal residue. 10cc syringe.

Price Each		RRP	4+	10+
H 1650A	10cc Syringe Gel	16.50	14.95	14.25
T 1927	12ml Pen	11.95	10.70	9.50

Chemtools® Vioflux Liquid Flux



General purpose acid based flux which is formulated for use with stainless steel, monel, high-chrome alloys, inconel, nickel, copper, brass, ferrous alloys, soft metals and many more. 250ml bottle.

Price Each	RRP	4+	10+
H 1651 250ml	25.00	23.00	20.50