

▼ Heatshrink Tubing

14pc Heatshrink Tubing Pack



Handy 300mm lengths of red & black heatshrink tubing in sizes from 1.5mm to 20mm diameter.

Price Per Pack	RRP	4+
W 0882 14pcs per pk	17.25	14.75

106pc Adhesive Heatshrink Pack



45mm & 75mm lengths of glue backed heatshrink. Sizes 3.2, 4.8, 6.4, 7.9, 9.5, 12.7mm (before shrinking). 3:1 shrink ratio.

Price Per Pack	RRP	3+	6+
W 0888 Red & Black	49.95	44.95	39.95

Handy Heatshrink Reels

Supplied on a spool for easy storage in your work space. Suitable for insulation, colour coding, strain relief and protection in electrical and electronic applications. Shrink ratio is 2:1. -55°C to +125°C.



Price Per Reel	RRP	3+	6+
W 0712 3mm Black 8m	11.50	10.50	9.15
W 0713 5mm Black 5m	11.50	10.50	9.15
W 0714 6mm Black 5m	11.50	10.50	9.15
W 0715 10mm Black 5m	11.50	10.50	9.15
W 0716 13mm Black 3m	11.50	10.50	9.15
W 0722 3mm Red 8m	11.50	10.50	9.15
W 0723 5mm Red 5m	11.50	10.50	9.15
W 0724 6mm Red 5m	11.50	10.50	9.15
W 0725 10mm Red 5m	11.50	10.50	9.15

Looking for heat guns?

Check out the tools section for a range of heat guns and blow torches. Great for heatshrinking!



PDF Downloads

Should you require any additional information on the operation or features of our products, you can find brochures, instructions and information in PDF format online at www.altronics.com.au.


Heatshrink Tubing On Rolls



Military grade flexible tubing. Suitable for insulation, colour coding, strain relief and protection. Continuous temperature rating is -55°C to 135°C and 300°C for short durations. 2:1 shrink ratio. Meets stringent requirements of MIL-I-23053/5 class one. Size indicated is the nominal diameter before shrinking.

Price Per Roll	Nom. Ø	Shrunk	Length	RRP	2+
Black					
WR0910A	1.5	0.75	200m	185.00	175.00
WR0912A	3	1.5	100m	125.00	115.00
WR0913A	5	2.5	100m	125.00	115.00
WR0914A	6	3	100m	145.00	130.00
WR0915A	10	5	50m	86.25	78.25
WR0916A	13	6.5	50m	135.00	125.00
WR0917A	19.1	10	50m	175.00	159.00
WR0919A	30	15	50m	199.00	179.00


Heatshrink With Glue Backing



Ideal for minimising cable movement and reducing moisture ingress into cable joins and plugs. 2:1 shrink ratio.

Price Per 1.2m Length	Nom Ø	Shrunk	RRP	4+	10+
Black					
W 0992A	3	1.5	5.20	4.65	4.15
W 0993A	5	2.5	5.70	5.20	4.60
W 0994A	6	3	6.30	5.70	5.10
W 0995A	10	5	7.50	6.75	6.00
W 0996A	13	6.5	8.55	7.50	6.60
W 0997A	19	9.5	11.50	10.50	9.15
W 0998A	30	15	14.50	13.05	11.60
W 0999A	50	25	27.95	25.15	22.35
Red					
W 1000	3	1.5	5.20	4.65	4.15
W 1001	5	2.5	5.70	5.20	4.60
W 1002	6	3	6.30	5.70	5.10
W 1003	10	5	7.50	6.75	6.00
W 1004	13	6.5	8.55	7.50	6.60
W 1005	19	9.5	11.50	10.50	9.15
W 1006A	30	15	14.50	13.05	11.60
W 1007A	50	25	27.95	25.15	22.35

Earthing Heatshrink Tubing (1.2m lengths)



Yellow & Green striped for denoting earth wiring.

Temperature rating: -55°C to 135°C
Shrink ratio: 2:1
Meets stringent requirements of MIL-I-23053/5 Class 1.

Price Per 1.2m Length	Nom. Ø	Shrunk	RRP	4+	10+
Green/Yellow (Earthing)					
W 0982	3	1.5	1.50	1.30	1.20
W 0983	5	2.5	1.95	1.85	1.65
W 0984	6	3	2.20	2.00	1.90
W 0985	10	5	3.35	3.10	2.90
W 0986	13	6.5	4.25	4.00	3.80
W 0987	20	10	6.30	5.65	5.20

Heatshrink Tubing (1.2m lengths)



Suitable for insulation, colour coding, strain relief and protection in electrical and electronic applications.

Temperature rating: -55°C to 135°C
Shrink ratio: 2:1
Meets stringent requirements of MIL-I-23053/5 Class 1.

Price Per 1.2m Length	Nom. Ø	Shrunk	RRP	4+	10+
Black ●					
W 0910A	1.5	0.75	1.95	1.75	1.60
W 0911A	2.4	1.2	2.10	1.90	1.70
W 0912A	3	1.5	2.20	2.00	1.80
W 0913A	5	2.5	2.30	2.15	1.95
W 0914A	6	3	2.55	2.35	2.20
W 0915A	10	5	3.35	3.10	2.90
W 0916A	13	6.5	4.25	4.00	3.80
W 0917A	20	10	6.30	5.65	5.20
W 0919A	30	15	12.50	11.25	10.00
W 0901A	50	25	18.95	17.25	15.25
Red ●					
W 0920A	1.5	0.75	1.95	1.75	1.60
W 0921A	2.4	1.2	2.10	1.90	1.70
W 0922A	3	1.5	2.20	2.00	1.80
W 0923A	5	2.5	2.30	2.15	1.95
W 0924A	6	3	2.55	2.35	2.20
W 0925A	10	5	3.35	3.10	2.90
W 0926A	13	6.5	4.25	4.00	3.80
W 0927A	20	10	6.30	5.65	5.20
W 0929A	30	15	12.50	11.25	10.00
Blue ●					
W 0930A	1.5	0.75	1.95	1.75	1.60
W 0932A	3	1.5	2.20	2.00	1.80
W 0933A	5	2.5	2.30	2.15	1.95
W 0934A	6	3	2.55	2.35	2.20
W 0935A	10	5	3.35	3.10	2.90
W 0936A	13	6.5	4.25	4.00	3.80
W 0937A	20	10	6.30	5.65	5.20
W 0939A	30	15	12.50	11.25	10.00
White ○					
W 0940A	1.5	0.75	1.95	1.75	1.60
W 0942A	3	1.5	2.20	2.00	1.80
W 0943A	5	2.5	2.30	2.15	1.95
W 0944A	6	3	2.55	2.35	2.20
W 0945A	10	5	3.35	3.10	2.90
W 0946A	13	6.5	4.25	4.00	3.80
W 0947A	20	10	6.30	5.65	5.20
W 0949A	30	15	12.50	11.25	10.00
Clear					
W 0950A	1.5	0.75	1.95	1.75	1.60
W 0952A	3	1.5	2.20	2.00	1.80
W 0953A	5	2.5	2.30	2.15	1.95
W 0954A	6	3	2.55	2.35	2.20
W 0955A	10	5	3.35	3.10	2.90
W 0956A	13	6.5	4.25	4.00	3.80
W 0957A	20	10	6.30	5.65	5.20
W 0959A	30	15	12.50	11.25	10.00
Green ●					
W 0960A	1.5	0.75	1.95	1.75	1.60
W 0962A	3	1.5	2.20	2.00	1.80
W 0963A	5	2.5	2.30	2.15	1.95
W 0965A	10	5	3.35	3.10	2.90
W 0966A	13	6.5	4.25	4.00	3.80
W 0967A	20	10	6.30	5.65	5.20
W 0969A	30	15	12.50	11.25	10.00
Yellow ●					
W 0970A	1.5	0.75	1.95	1.75	1.60
W 0972A	3	1.5	2.20	2.00	1.80
W 0973A	5	2.5	2.30	2.15	1.95
W 0974A	6	3	2.55	2.35	2.20
W 0975A	10	5	3.35	3.10	2.90
W 0976A	13	6.5	4.25	4.00	3.80
W 0977A	20	10	6.30	5.65	5.20
W 0979A	30	15	12.50	11.25	10.00