

▼ Figure 8 Hook Up Cable

14AWG Double Insulated Heavy Duty



Size: 2 x 28/0.30
Voltage rating: 300V AC @ 12A
Dimensions: ≈4.0 x 7.0mm
Conductor: 2.0mm² (≈14AWG)
Jacket material: PVC
Resistance: 0.0093Ω/m @ 20°C
Temperature rating: 75°C

Ideal for running power in automotive applications. Double sheath for added protection.

Price Per	RRP (m)	Roll
W 4150 100m Roll	4.50	425.00
W 4152 300m Roll	4.50	1275.00
W 4170 100m Roll Tinned	4.65	440.00

12AWG Double Insulated Heavy Duty



Huge 20A current rating. Double sheath for added protection.

Size: 2 x 56/0.30
Voltage rating: 300V AC @ 20A
Dimensions: ≈5.6 x 9.2mm
Conductor: 4.0mm² (≈12AWG)
Jacket material: PVC
Resistance: 0.0047Ω/m @ 20°C
Temperature rating: 75°C

Price Per	RRP (m)	Roll
W 4154 100m Roll	6.50	520.00

10AWG Double Insulated Heavy Duty



For high current auto and marine power. Double sheath for added protection.

Size: 2 x 85/0.30
Voltage rating: 300V AC @ 28A
Dimensions: ≈6.4 x 10.8mm
Conductor: 6.0mm² (≈10AWG)
Jacket material: PVC
Resistance: 0.0031Ω/m @ 20°C
Temperature rating: 75°C

Price Per	RRP (m)	Roll
W 4158 100m Roll	8.50	775.00

8AWG Double Insulated Heavy Duty



For high current auto and marine power. Double sheath for added protection.

Size: 2 x 112/0.30
Voltage rating: 300V AC @ 80A
Dimensions: ≈7.6 x 13.2mm
Conductor: 8.0mm² (≈8AWG)
Jacket material: PVC
Resistance: 0.0031Ω/m @ 20°C
Temperature rating: 75°C

Price Per	RRP (m)	Roll
W 4162 100m Roll	15.75	1425.00

15AWG Double Insulated Cable



Double insulated cable suitable for use in fire alarm and heavy duty public address systems. All metre marked.

Size: 2 x 7/0.5
Rating: 600V AC @ 14A
Twisted Pair Dimensions: ≈6.8 x 4.5mm
Untwisted Pair Dimensions: ≈9.4 x 5mm
Conductor: 1.4mm² (≈15AWG)
Jacket material: PVC
Resistance: 0.0132Ω/m @ 20°C
Temperature rating: 75°C

Price Per	RRP (m)	Roll
Twisted Pair		
W 6002 300m Roll Red	2.00	570.00
W 6003 500m Roll Red	2.65	1075.00
Untwisted Pair		
W 2190 300m Roll White	2.55	540.00
W 2191 500m Roll White	2.55	900.00

18AWG Double Insulated Cable



Standard double insulated cable for 100V line PA installs. 6 colours. All metre marked.

Size: 2 x 24/0.20
Voltage rating: 600V AC @ 7.5A
Dimensions: ≈6 x 3.5mm
Conductor: 0.75mm² (≈18AWG)
Jacket material: PVC
Resistance: 0.0245Ω/m @ 20°C
Temperature rating: 75°C

Colour	100m	200m	300m	500m
■ Red	-	-	W 2150	-
□ White	W 2153	W 2154	W 2155	W 2156
■ Brown	W 2158	W 2159	W 2160	W 2161
■ Grey	W 2163	W 2164	W 2165	W 2166
■ Yellow	W 2168	W 2169	W 2170	W 2171
■ Black	W 2172	W 2173	W 2174	W 2176

Price Per	RRP (m)	Roll
100m Roll	2.15	190.00
200m Roll	2.15	389.00
300m Roll	2.15	570.00
500m Roll	2.15	950.00

17AWG Double Insulated Cable



Standard double insulated cable for 100V line PA installs. Heavier duty allows for longer runs. All metre marked.

Size: 2 x 32/0.20
Rating: 600V AC @ 10A
Dimensions: ≈6.8 x 4mm
Conductor: 1mm² (≈17AWG)
Jacket material: PVC
Resistance: 0.01802Ω/m @ 20°C
Temperature rating: 75°C

Price Per	RRP (m)	Roll
300m Roll	2.10	450.00
500m Roll	2.10	725.00

▼ Speaker Cable

18AWG Flat Cable Oxygen Free



This low profile 18AWG cable allows running of speaker wiring under carpet and rugs.

Size: 2 x 96/0.1
Dimensions: ≈2.5 x 12.5mm
Conductor: 0.75mm² (≈18AWG)
Jacket material: PVC
Resistance: 0.016Ω/m @ 20°C
Temperature rating: 90°C

Price Per	RRP (m)	Roll
W 2980 50m Roll	2.85	100.00
W 2981 100m Roll	2.85	200.00

17AWG "Whopper" Cable Oxygen Free




Our most popular choice for home hi-fi and theatre use. Translucent outer sheath with blue trace.

Size: 2 x 102/0.12
Dimensions: ≈4.0 x 8.3mm
Conductor: 1.15mm² (≈17AWG)
Jacket material: PVC
Resistance: 0.016Ω/m @ 20°C
Temperature rating: 90°C

Price Per	RRP (m)	Roll
W 2140 50m Roll	3.50	157.50
W 2141 100m Roll	3.50	315.00

14AWG "Whopper" Cable Low Loss



A 14AWG cable for speaker connection cable featuring translucent outer sheath.

Size: 2 x 90/0.18
Dimensions: ≈4.0 x 8.3mm
Conductor: 2.29mm² (≈14AWG)
Jacket material: PVC
Resistance: 0.0081Ω/m @ 20°C
Temperature rating: 90°C

Price Per	RRP (m)	Roll
W 2130 50m Roll	4.50	162.50
W 2132 100m Roll	4.50	325.00

12AWG "Whopper" Cable Oxygen Free



A no compromises 12AWG high power hi-fi speaker cable with durable translucent outer sheath.

Size: 2 x 315/0.12
Dimensions: ≈6.0 x 12mm
Conductor: 3.56mm² (≈12AWG)
Jacket material: PVC
Resistance: 0.0052Ω/m @ 20°C
Temperature rating: 90°C

Price Per	RRP (m)	Roll
W 2145 50m Roll	6.85	287.50
W 2146 100m Roll	6.85	575.00